

ZPMV2.E59552 - Wiring, Printed - Component

Wiring, Printed - Component


[See General Information for Wiring, Printed - Component](#)**BAY AREA CIRCUITS INC**44358 OLD WARM SPRNG BLVD
FREMONT, CA 94538 USA

E59552

Type	Cond Width		Cond Thk mic(mil)	SS/ DS/ DSO	Max Area Diam mm(in)	Solder		Max		Meets UL796 DSR	C T I
	Min mm(in)	Min Edge mm(in)				Limits C sec	Oper Temp C	Flame Class			
Mass laminated packages.											
C	0.08 (0.003)	0.2 (0.008)	17 (0.67)	DS	101.6 (4.0)	260	10	130	V-0	All	3
Multilayer printed wiring boards.											
2	0.08 (0.003)	0.2 (0.008)	17.3 (0.68)	DS	101.6 (4.0)	260	10	130	V-0	All	-
2A	0.08 (0.003)	0.2 (0.008)	17.3 (0.68)	DS	101.6 (4.0)	260	10	120	V-0	All	-
4-1	0.1 (0.004)	0.12 (0.005)	17 (0.67) Int:102	DS	50.8 (2.0)	270	10	130	V-0	All	-
D	0.08 (0.003)	0.08 (0.003)	17 (0.67) Int:68	DS	102 (4.0)	288	20	130	V-0	All	3
M-10	0.07 (0.003)	0.12 (0.005)	17 (0.67) Int:213	DS	76.2 (3.0)	260	10	130	V-0	All	3
M-20	0.09 (0.004)	0.12 (0.005)	17 (0.67) Int:213	DS	76.2 (3.0)	280	20	130	V-0	All	3
M-9	0.07 (0.003)	0.12 (0.005)	17 (0.67) Int:68	DS	76.2 (3.0)	260	10	130	V-0	All	*
MA	0.075 (0.003)	0.075 (0.003)	12 (0.47) Int:34	DS	76.2 (3.0)	288	20	140	HB	All	4

Multilayer printed wiring boards, flammability only recognition.											
MR	-	-	-	DS	-	288	20	-	V-0	-	-
Single layer printed wiring boards.											
1	0.08 (0.003)	0.2 (0.008)	17.3 (0.68)	DS	101.6 (4.0)	260	10	130	V-0	All	-
1A	0.08 (0.003)	0.2 (0.008)	17.3 (0.68)	DS	101.6 (4.0)	260	10	120	V-0	All	-
3-1	0.1 (0.004)	0.12 (0.005)	17 (0.67)	DS	50.8 (2.0)	270	10	130	V-0	All	*
D-10	0.1 (0.004)	0.15 (0.006)	17 (0.67)	DS	76.2 (3.0)	260	10	130	V-0	All	*
D-20	0.12 (0.005)	0.12 (0.005)	17 (0.67)	DS	76.2 (3.0)	288	20	130	V-0	All	3
D-9	0.07 (0.003)	0.13 (0.005)	17 (0.67)	DS	76.2 (3.0)	260	10	130	V-0	All	*
F	0.08 (0.003)	0.08 (0.003)	34 (1.34)	DS	76.2 (3.0)	260	10	105	V-0	All	*
G	0.08 (0.003)	0.08 (0.003)	17 (0.67)	DS	76.2 (3.0)	260	10	105	V-0	All	*

* - CTI marking is optional and may be marked on the printed wiring board.

Marking: Company name or tradename "BAC in a rectangle" or trademark  or file number and type designation. May be followed by a suffix to denote factory identification or burning test classification.

Last Updated on 2020-09-10

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2020 UL LLC"